

# Datasheet

## TERM2000 COLOR IP67



Code	Wattage	MaterialColor	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Features	Cable	Connection	Heatable area in m <sup>2</sup>	Mounting	Spare tube
URCAC150V9010	1 x 1,50 kW	White	4260051485607	IP67	61 x 9,5 x 12,5	2000	2,4	1,9m 3-wire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	12-13	Wall and ceiling	ULG1500V
URCAC165V9010	1 x 1,65 kW	White	4260051485614	IP67	61 x 9,5 x 12,5	2000	2,4	1,9m 3-wire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	13-14	Wall and ceiling	ULG1650V
URCAC200V9010	1 x 2,0 kW	White	4260051485621	IP67	61 x 9,5 x 12,5	2000	2,4	1,9m 3-wire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	Wall and ceiling	ULG2001V
URCAC150V9005	1 x 1,5 kW	Black	4260051486222	IP67	61 x 9,5 x 12,5	2000	2,4	1,9m 3-wire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	12-13	Wall and ceiling	ULG1500V
URCAC165V9005	1 x 1,65 kW	Black	4260051486239	IP67	61 x 9,5 x 12,5	2000	2,4	1,9m 3-wire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	13-14	Wall and ceiling	ULG1650V
URCAC200V9005	1 x 2,0 kW	Black	4260051486246	IP67	61 x 9,5 x 12,5	2000	2,4	1,9m 3-wire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	Wall and ceiling	ULG2001V
URCAC150V7016	1 x 1,5kW	Anthracite	4260051488240	IP67	61 x 9,5 x 12,5	2000	2,4	1,9m 3-wire 1,5mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230V 50Hz	12-13	Wall and ceiling	ULG1500V

**AUSSTATTUNG:**

- 1 = PERFECTCLIME
- 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht)
- 3 = NO GLARE (100% Lichtreduktion)
- 4 = Wasserdicht
- 5 = Licht
- 6 = LOW GLARE

URCAC165V7016	1 x 1,65kW	Anthracite	4260051488257	IP67	61 x 9,5 x 12,5	2000	2,4	1,9m 3-wire 1,5mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230V 50Hz	13-14	Wall and ceiling	ULG1650V
URCAC200V7016	1 x 2,0kW	Anthracite	4260051486581	IP67	61 x 9,5 x 12,5	2000	2,4	1,9m 3-wire 1,5mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230V 50Hz	14-16	Wall and ceiling	ULG2001V

