

Datasheet

TERM2000 IP67 Aluminum polished



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Feature	Kabel	Connection	Heatable area in m ²	Spare tube	Mounting
RCA100	1,0 kW	Alu polished	4260051480503	IP67	45 x 9,5 x 12,5	2000	4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	9-11	LG1001	Wall and ceiling
RCA165	1,65 kW	Alu polished	4260051480237	IP67	61 x 9,5 x 12,5	2300	4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	13-14	LG1650	Wall and ceiling
RCA200V	2,0 kW	Alu polished	4260051480275	IP67	61 x 9,5 x 12,5	2300	4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LG2001V	Wall and ceiling
URCA100V	1,0 kW	Alu polished	4260051485577	IP67	45 x 9,5 x 12,5	2300	2, 4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	9-11	ULG1001V	Wall and ceiling
URCA150V	1,5kW	Alu polished	4260051485386	IP67	61 x 9,5 x 12,5	2300	2,4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	12-13	ULG1500V	Wall and ceiling



URCA165V	1,65 kW	Alu polished	4260051483863	IP67	61 x 9,5 x 12,5	2300	2, 4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	13-14	ULG1650V	Wall and ceiling
URCA200V	2,0 kW	Alu polished	4260051484150	IP67	61 x 9,5 x 12,5	2300	4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall and ceiling

AUSSTATTUNG: 1 = PERFECTCLIME | 2 = ULTRA LOW GLARE  (100% Wärme bei 80% weniger Licht) | 3 = NO GLARE  (100% Lichtreduktion!) | 4 = Wasserdicht  | 5 = Licht  | 6 = LOW GLARE 