

# Datasheet

## TERM2000 L&H 200cm IP65



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Features	Cable	Connection	Heatable area in m <sup>2</sup>	Spare tube	Mounting
URLH4265	2 x 2,0kW + 14W	Alu polished	4260051484075	IP65	200 x 9,5 x 12,5	7100	2, 4, 5	2m 5-wire 2,5mm <sup>2</sup> , Wire-end sleeves	3/N/PE ~ 235 V 50 Hz	28-30	ULG2001V	Wall and ceiling
URLHC42659010	2 x 2,0kW + 14W	White	4260409691575	IP65	200 x 9,5 x 12,5	7100	2, 4, 5	2m 5-wire 2,5mm <sup>2</sup> , Wire-end sleeves	3/N/PE ~ 235 V 50 Hz	28-30	ULG2001V	Wall and ceiling
URLHC42659005	2 x 2,0kW + 14W	Black	4260409691582	IP65	200 x 9,5 x 12,5	7100	2, 4, 5	2m 5-wire 2,5mm <sup>2</sup> , Wire-end sleeves	3/N/PE ~ 235 V 50 Hz	28-30	ULG2001V	Wall and ceiling
URLHC42657016	2 x 2,0kW + 14W	Anthrazite	4260409692602	IP65	200 x 9,5 x 12,5	7100	2, 4, 5	2m 5-wire 2,5mm <sup>2</sup> , Wire-end sleeves	3/N/PE ~ 235 V 50 Hz	28-30	ULG2001V	Wall and ceiling

**AUSSTATTUNG:**

- 1 = PERFECTCLIME
- 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht)
- 3 = NO GLARE (100% Lichtbeduktanz)
- 4 = Wasserdicht
- 5 = Licht
- 6 = LOW GLARE