

Data sheet

MODULAR SINGLE MODULS



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Features	Cable	Connection	Heat-able m ²	Spare tube	Mounting
MRL2C9010	2 x 3,5 Watt	White	4260409691605	65	100 x 9,5 x 12,5	2000	4,5	1,9m 3-wired 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz		ULG2001V	Wall and ceiling
MRL2C9005	2 x 3,5 Watt	Black	4260409693098	65	100 x 9,5 x 12,5	2000	4,5	1,9m 3-wired 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz		ULG2001V	Wall and ceiling
MRL2C7016	2 x 3,5 Watt	Anthracite	4260409691629	65	100 x 9,5 x 12,5	2000	4,5	1,9m 3-wired 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz		ULG2001V	Wall and ceiling
MURCAC200V9010	1 x 2 kW	White	4260409691520	67	100 x 9,5 x 12,5	2300	2,4	1,9m 3-wired 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall and ceiling
MURCAC200V9005	1 x 2 kW	Black	4260409693104	67	100 x 9,5 x 12,5	2300	2,4	1,9m 3-wired 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall and ceiling
MURCAC200V7016	1 x 2 kW	Anthracite	4260409691513	67	100 x 9,5 x 12,5	2300	2,4	1,9m 3-wired 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall and ceiling
MURLHC21659010	1 x 2 kW + 2 x 3,5 Watt	White	4260409691551	65	100 x 9,5 x 12,5	2400	2,4,5	1,0m 5-wired 1,5mm ² , Schuko plug	1/N/PE ~ 230V 50Hz	14-16	ULG2001V	Wall and ceiling
MURLHC21659005	1 x 2 kW + 2 x 3,5 Watt	Black	4260409691544	65	100 x 9,5 x 12,5	2400	2,4,5	1,0m 5-wired 1,5mm ² , Schuko plug	1/N/PE ~ 230V 50Hz	14-16	ULG2001V	Wall and ceiling
MURLHC21657016	1 x 2 kW + 2 x 3,5 Watt	Anthracite	4260409691568	65	100 x 9,5 x 12,5	2400	2,4,5	1,0m 5-wired 1,5mm ² , Schuko plug	1/N/PE ~ 230V 50Hz	14-16	ULG2001V	Wall and ceiling

AUSSTATTUNG: 1 = PERFECTCLIME | 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht) | 3 = NO GLARE (100% Lichtreduktion) | 4 = Wasserdicht | 5 = Licht | 6 = LOW GLARE

Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Features	Cable	Stromanschluss	Heat-able m ²	Spare tube	Mounting
M50BL9005		Black	4260409693210	67	50 x 9,5 x 12,5	80	4					
M50BL7016		Anthracite	4260409693227	67	50 x 9,5 x 12,5	80	4					
M75BL9010		White	4260409693234	67	75 x 9,5 x 12,5	120	4					
M75BL9005		Black	4260409693241	67	75 x 9,5 x 12,5	120	4					
M75BL7016		Anthracite	4260409693258	67	75 x 9,5 x 12,5	120	4					
M100BL9010		White	4260409693265	67	100 x 9,5 x 12,5	160	4					
M100BL9005		Black	4260409693272	67	100 x 9,5 x 12,5	160	4					
M100BL7016		Anthracite	4260409693289	67	100 x 9,5 x 12,5	160	4					

AUSSTATTUNG:

- 1 = PERFECTCLIME
- 2 = ULTRA LOW GLARE 
(100% Wärme bei 80% weniger Licht)
- 3 = NO GLARE 
(100% Lichtreduktion!)
- 4 = Wasserdicht 
- 5 = Licht 
- 6 = LOW GLARE 

MODULAR SYSTEME



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Features	Cable	Connection	Heat-able m²	Spare tube	Mounting
MSET3.1 9010	1 x 2 kW + 4 x 3,5 Watt	White	4260409691636	65	300 x 9,5 x 12,5	7100	2,4,5	1,0m 5-wired 1,5mm², Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	14-16	ULG2001V	Wall and ceiling
MSET3.1 9005	1 x 2 kW + 4 x 3,5 Watt	Black	4260409692831	65	300 x 9,5 x 12,5	7100	2,4,5	1,0m 5-wired 1,5mm², Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	14-16	ULG2001V	Wall and ceiling
MSET3.1 7016	1 x 2 kW + 4 x 3,5 Watt	Anthracite	4260409691643	65	300 x 9,5 x 12,5	7100	2,4,5	1,0m 5-wired 1,5mm², Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	14-16	ULG2001V	Wall and ceiling
MSET3.2 9010	2 x 2 kW + 2 x 3,5 Watt	White	4260409691858	65	300 x 9,5 x 12,5	7000	2,4,5	1,0m 5-wired 1,5mm², Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	28-30	ULG2001V	Wall and ceiling
MSET3.2 9005	2 x 2 kW + 2 x 3,5 Watt	Black	4260409692848	65	300 x 9,5 x 12,5	7000	2,4,5	1,0m 5-wired 1,5mm², Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	28-30	ULG2001V	Wall and ceiling
MSET3.2 7016	2 x 2 kW + 2 x 3,5 Watt	Anthracite	4260409691872	65	300 x 9,5 x 12,5	7000	2,4,5	1,0m 5-wired 1,5mm², Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	28-30	ULG2001V	Wall and ceiling
MSET3.3 9010	3 x 2 kW	White	4260409692657	67	300 x 9,5 x 12,5	6900	2,4	1,0m 5-wired 1,5mm², Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	42-44	ULG2001V	Wall and ceiling

AUSSTATTUNG:

1 = PERFECTCLIME

2 = ULTRA LOW GLARE
(100% Wärme bei 80% weniger Licht)

3 = NO GLARE
(100% Lichtreduktion!)

4 = Wasserdicht

5 = Licht

6 = LOW GLARE

Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Features	Cable	Connection	Heat-able m ²	Spare tube	Mounting
MSET3.3 9005	3 x 2 kW	Black	4260409692664	67	300 x 9,5 x 12,5	6900	2,4	1,0m 5-wired 1,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	42-44	ULG2001V	Wall and ceiling
MSET3.3 7016	3 x 2 kW	Anthracite	4260409692688	67	300 x 9,5 x 12,5	6900	2,4	1,0m 5-wired 1,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	42-44	ULG2001V	Wall and ceiling
MSET4.1 9010	2 x 2 kW + 4 x 3,5 Watt	White	4260409692695	65	400 x 9,5 x 12,5	9400	2,4,5	1,0m 5-wired 1,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	28-30	ULG2001V	Wall and ceiling
MSET4.1 9005	2 x 2 kW + 4 x 3,5 Watt	Black	4260409692701	65	400 x 9,5 x 12,5	9400	2,4,5	1,0m 5-wired 1,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	28-30	ULG2001V	Wall and ceiling
MSET4.1 7016	2 x 2 kW + 4 x 3,5 Watt	Anthracite	4260409692725	65	400 x 9,5 x 12,5	9400	2,4,5	1,0m 5-wired 1,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	28-30	ULG2001V	Wall and ceiling
MSET4.2 9010	2 x 2 kW + 4 x 3,5 Watt	White	4260409692732	65	400 x 9,5 x 12,5	9400	2,4,5	1,0m 5-wired 1,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	28-30	ULG2001V	Wall and ceiling
MSET4.2 9005	2 x 2 kW + 4 x 3,5 Watt	Black	4260409692749	65	400 x 9,5 x 12,5	9400	2,4,5	1,0m 5-wired 1,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	28-30	ULG2001V	Wall and ceiling
MSET4.2 7016	2 x 2 kW + 4 x 3,5 Watt	Anthracite	4260409692763	65	400 x 9,5 x 12,5	9400	2,4,5	1,0m 5-wired 1,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	28-30	ULG2001V	Wall and ceiling
MSET5.1 9010	2 x 2 kW + 6 x 3,5 Watt	White	4260409692770	65	500 x 9,5 x 12,5	11800	2,4,5	1,0m 5-wired 1,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	28-30	ULG2001V	Wall and ceiling
MSET5.1 9005	2 x 2 kW + 6 x 3,5 Watt	Black	4260409692787	65	500 x 9,5 x 12,5	11800	2,4,5	1,0m 5-wired 1,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	28-30	ULG2001V	Wall and ceiling
MSET5.1 7016	2 x 2 kW + 6 x 3,5 Watt	Anthracite	4260409692800	65	500 x 9,5 x 12,5	11800	2,4,5	1,0m 5-wired 1,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50Hz	28-30	ULG2001V	Wall and ceiling

AUSSTATTUNG:

1 = PERFECTCLIME

2 = ULTRA LOW GLARE
(100% Wärme bei 80% weniger Licht)

3 = NO GLARE
(100% Lichtreduktion!)

4 = Wasserdicht

5 = Licht

6 = LOW GLARE

Burda Worldwide Technologies GmbH – Rudolf-Diesel-Straße 18 – 65760 Eschborn – T: +49 6173 324240 – F: +49 6173 3242424 – info@burdawtg.de –

www.burdawtg.de